

22. (New) The sensor unit according to claim 12, wherein the light guide body is integrated into a light guide body of a rain sensor device.

23. (New) The sensor unit according to claim 22, wherein the light guide body is made in a multicomponent injection molding process, together with the light guide body of the rain sensor device and a coupling medium.

Remarks

This Preliminary Amendment cancels without prejudice claims 1-11, in the underlying PCT Application No. PCT/DE00/01989, and adds new claims 12-23. The new claims conform the claims to U.S. Patent and Trademark Office rules and do not add new matter to the application.

In accordance with 37 C.F.R. § 1.121(b)(3), the Substitute Specification (including the Abstract, but without the claims) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to U.S. Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. § 1.121(b)(3)(iii) and § 1.125(b)(2), a Marked Up Version Of The Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) is respectfully requested.


The underlying PCT Application No. PCT/DE00/01989 includes an International Search Report, dated November 6, 2000. The Search Report includes a list of documents that were uncovered in the underlying PCT Application. A copy of the Search Report accompanies this Preliminary Amendment.

The underlying PCT Application No. PCT/DE00/01989 also includes an International Preliminary Examination Report, dated April 24, 2001, a copy of which is included, including a translation.


Applicants assert that the subject matter of the present application is new, non-obvious, and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully Submitted,

KENYON & KENYON

By:  Reg. No. 22,490

Dated: 1/16/02

By: 
Richard L. Mayer
(Reg. No. 22,490)

One Broadway
New York, NY 10004
(212) 425-7200

[10191/2202]

LIGHT-SENSITIVE SENSOR UNIT, IN PARTICULAR FOR AUTOMATIC SWITCHING OF LIGHTING DEVICES

Field Of The Invention

The present invention relates to a light-sensitive sensor unit, in particular for automatic switching of lighting devices in vehicles.

5 Background Information

[The present invention relates to a light-sensitive sensor unit, in particular for automatic switching of lighting devices in vehicles, according to the definition of the species of Claim 1.

10]Such a sensor unit is known from German Patent No. 195 23 262.3, which includes a global sensor and a directional sensor for detecting the lighting conditions outside the vehicle. The sensor unit is connected to the analyzer unit which determines from the signals of the sensor unit whether a change in the circuit state of the lighting device is necessary under the given lighting conditions prevailing in the surroundings of the vehicle. Although this known sensor unit permits automatic
 15 switching of the lighting device, it includes a relatively large number of parts due to the global sensors and the directional sensors, and this means a high cost and expensive adjustment.

[Advantages of the] Summary Of The Invention

20 The device according to the present invention [having the features of Claim 1] has the advantage that a simple, compact, robust, easy-to-assemble and practically adjustment-free sensor unit is available due to the integration of the global and directional sensors. Furthermore, the device includes only a minimal number of components, which permits simple and inexpensive production with expanded
 25 functionality. The small dimensions which are possible due to the integration of the global and directional sensors have proven to be another major advantage, because

MARKED-UP VERSION OF SUBSTITUTE SPECIFICATION

8L244510440

the size of components on the windshields of motor vehicles which interfere with vision should be minimized.

[Advantageous refinements of the sensor unit according to the main claim are possible through the features characterized in the subclaims.]

5 Due to the fact that at least three sensors detect light from predetermined directions, a wider range in front of the vehicle is detected. If at least one sensor is arranged in the direction of travel and the two other sensors are arranged, pivoted out of the direction of travel by an angle α on both sides, this yields a wide cone of detection in front of the vehicle, so that even the entrance of a tunnel which is not yet in the
10 direction of travel can be detected and the lighting devices controlled accordingly.

If the directional sensors have lens-like elements, which may also have a smooth transition between them, the detection cone may be adjusted individually to the wishes of the automobile manufacturer.

15 Integration of the light guide body of the sensor unit into a light guide body of a rain sensor device makes it possible to eliminate additional components and to further reduce the number of components on the windshield which interfere with vision, in particular when the light guide body is manufactured in a multicomponent injection
20 molding process together with the light guide body of the rain sensor and the coupling medium.

Brief Description Of The Drawings [of the Drawing]

25 An embodiment of the present invention is illustrated in Figs. 1 and 2 and explained in greater detail in the following description.]

Fig. 1 shows a section through a sensor unit according to the present invention[, and].

30 Fig. 2 shows a diagram of the sensor unit integrated into a light guide body of a rain

sensor in a perspective view.

Detailed Description [of the Embodiment]

5 Fig. 1 shows a sensor unit 10 according to the present invention, mounted on a windshield 11, in particular a windshield of a motor vehicle. Sensor unit 10 is composed of multiple sensors 12, each sensor 12 including a sensor element 13 and a light guide element 14, 14a. However, two light guide elements 14 here together use one sensor element 13, so that there are three light-sensitive sensor elements 13 having four light guide elements 14 and 14a. The light guide body on
10 which light guide elements 14, 14a are mounted is composed of an at least partially transparent plate having cylindrical recesses sealed with lens-shaped round bodies. These cylindrical recesses together with the lens-shaped round bodies form a light guide element 14, 14a. If parallel light passes through the lens-shaped round bodies along the center axis of the cylindrical recesses, it yields a focal point f which
15 characterizes a focal distance of light guide element 14, 14a.

Sensor elements 13 are each arranged between focal points f of light guide elements 14 and light guide elements 14 themselves. This yields a light detection cone directed forward in the direction of travel, allowing detection in predetermined
20 directions. The cone angle of the light detection cone can be adjusted through the distance between focal points f of respective light guide element 14 and light-sensitive sensor elements 13.

An analyzer unit 15 controls the switching of a lighting device 16 as a function of the
25 signals of sensor elements 13. Sensor elements 13 may be mounted jointly to a circuit board 17 and are preferably designed to permit a differentiation between daylight and artificial light to prevent a shutdown due to artificial lighting in a tunnel, for example. This can be accomplished through a suitable choice of the sensitivity range of sensor elements 13. It is also possible to select the sensitivity range so that
30 certain spectral ranges or characteristic lines, e.g., of gas discharge lamps, are

detected, thus permitting control of the high and low beams in a motor vehicle.

In addition to these directional sensors, at least one light guide element 14a is aimed forward but not necessarily in the direction of travel. The light detection cone of this minimum of one light guide element 14a has a very large cone angle and detects global lighting conditions outside the vehicle.

All light guide elements 14, 14a, in particular the sensors of the global sensors and directional sensors, are combined in one piece in a light guide body 18. This light guide body 18 may be manufactured as an injection molded part of transparent or UV-permeable plastic. It is likewise possible to manufacture light guide body 18 of a pigmented or coated plastic which includes an optionally desired filter effect for influencing the sensitivity range of the sensor. This light guide body is pressed onto the windshield over a coupling medium 19, e.g., a silicone pad. Coupling medium 19 prevents air inclusions between windshield 11 and light guide body which would cause unwanted scattering. It is also possible to apply coupling medium 19 directly to light guide body 18 in the manufacture thereof in a multicomponent injection molding process.

Abstract [of the] Of The Disclosure

5 A light-sensitive sensor unit, in particular for automatic switching of lighting devices, preferably in motor vehicles, including at least two light-sensitive sensors, at least one first sensor detecting the global lighting conditions, and at least one second sensor detecting the lighting conditions in predetermined directions. All light guide elements provided for the sensors are joined in one piece to form a light guide body.

(Fig. 1)]

. 439676